

GF





GORDINI



PLANER



TECHNICAL SPECIFICATION

Model	Standard Flow	High Flow Medium Power					High Flow High Power		
		CP 40.13	CP 40.15	CP 45.15	CP 50.15	CP 55.15	CP 50.17	CP 60.17	CP 100.15
Working width standard drum	mm	400	400	450	500	550	500	600	1000
Working depth standard drum	mm	0 - 125	0 - 150			0 - 170			0 - 150
Standard asphalt picks	n.	48	51	54	57	60	60	66	88
Oil flow, min-max ⁽¹⁾	lt/min	45 - 80	90 - 140		100 - 140		120 - 160		
Oil pressure, max-min ⁽¹⁾	bar	240 - 170	300 - 170			300 - 170			
Weight standard configuration	kg	540	750	770	790	810	850	890	1100
Minimum distance from wall	mm	60	60			60			
Independent depth adjustment Right and Left		mechanical/hydraulic ⁽²⁾							
Right and Left sideshift	mm	600 mechanical ⁽³⁾	650 hydraulic			650 hydraulic			
20° transversal angle		---	mechanical/hydraulic ⁽²⁾			mechanical/hydraulic ⁽²⁾			
Average milling speed ((standard drum at 50% depth)	mt/min	0,6 - 3,5	1,2 - 5,5	1,0 - 5,0	0,9 - 4,6	0,8 - 4,2	1,0 - 4,5	0,9 - 4,0	0,7 - 4,5
	ton	2,3 - 3,5	2,3 - 3,2			3,0 - 4,8			
	ton	3,0 - 5,5	4,5 - 6,5			7,0 - 9,0			
	ton	3,5 - 6,0	5,0 - 7,5			6,0 - 8,5			
Overall size in standard configuration		A cm B cm C cm	150 83 100	160 88 106			160 88 106		

⁽¹⁾ Hydraulic system flow and pressure must be inversely proportional

⁽²⁾ On request

⁽³⁾ Hydraulic on request



G.F. Gordini srl

Via E. Mattei, 4 - 48012 Bagnacavallo RA - Italy

tel. +39 0545 62712 fax +39 0545 62140

info@gfgordini.com - www.gfgordini.com

ACCESSORI PER MACCHINE OPERATRICI

Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.